Elevator Canopy Lift by Telpro Inc.



Protects Workers
Protects Canopies Speeds Installation

CAPACITY:

- 600 lb capacity
- 9'max height

POWER SUPPLY:

- 12v DC rechargeable battery
- 110v AC Trickle charger included

LIFT SYSTEM:

- Patented hydraulic powered telescoping chain lift mechanism
- Adjustable variable speed for complete control
- Removable pump unit

SAFETY FEATURES:

- Patent pending constant pressure ratcheting redundant safety mechanism
- Integrated overload bypass valve prevents overloading lift and provides total descent
- Remote operator control pendant
- Hydraulic system can be closed to offer additional safety when the lift is loaded

CONVENIENCE FEATURES:

- Handles a wide range of canopy assembly dimensions
- Can rotate to 15 degrees for vertical entry through door opening
- Unique tilt mechanism provides complete control while positioning canopy assemblies



Simple one person assembly in just a few minutes, no tools required.



One worker can maneuver loaded lift to safely and rapidly raise the canopy assembly into place.



Long cord on the remote pendant station allows the installer to stand outside the hoistway as the canopy is being lifted into position.

Over 40 years ago **Telpro inc.** changed the way the world installs drywall with our line of **PANELIFT** brand drywall lifts. Now we're going to work for the elevator construction industry.

The revolutionary patent pending

Talpro Inc. Model 294 material lift drastically improves operator safety, ergonomics and productivity when installing elevator canopy assemblies.

The **Telpro inc.** Model 294 is a special order item. Call now for pricing and to schedule production of your new lift!

Protects Workers
Protects Canopies
Speeds Installation

Manufactured in the USA by

Telpro Inc.

7251 S 42nd St
Grand Forks, ND 58201
701-775-0551
telpromktg@telproinc.com
www.telproinc.com